

LENMAR™

FINE WOOD FINISHES



UltraMax High Solids Precat • Water White Precat Vinyl Sealers
White Precat Topcoats • White Precat Undercoaters

UltraLaq™ Precatalyzed Clear Systems

The UltraLaq series of precatalyzed lacquers includes both the UltraMax High Solids Precatalyzed Lacquer and the UltraLaq Premium Precatalyzed Lacquer. The UltraMax, 1D.35X series, is a self-sealing, high solids system which offers excellent chemical and moisture resistance. While the product is formulated ready to spray, it can alternatively be catalyzed with the 1A.822B Catalyst to achieve quicker cure times, and if catalyzed, the UltraMax line has a 120 day pot-life. The UltraLaq, 1D.33X line of Premium Precatalyzed Lacquers is a 27% solids, self-sealing system that offers an ease of application and tough, chemically resistant film quality unparalleled in the industry. This product combines the ability to achieve beautiful finishes with the highest quality and durability available. Both systems easily surpass the requirements of the KCMA standards, and are HAP and VOC compliant.



UltraLaq™ Precatalyzed White Systems

The UltraLaq white precatalyzed system consists of the 1C.800 Precatalyzed White Primer and the 1M.80X series of Precatalyzed White Topcoats. The 1C.800 undercoat is a high solids, 41% NVM undercoater designed to promote adhesion and fill grain. It has excellent sandability and moisture resistance and is an ideal foundation for the white precatalyzed topcoats. The 1M.80X line, premium quality white topcoats have excellent flow, leveling, and surface slip, while offering durability, chemical and moisture resistance. Both products are VOC and HAP compliant, and a 3 coat finishing system will pass the requirements of the KCMA standards. Both undercoater and topcoat can be tinted to achieve off-white finishes, and the QuickStain glaze is ideal for use with this system.



UltraLaq™ Sealers

While all UltraLaq clear products are designed to be self-sealed, the UltraLaq line offers two vinyl sealers for use in more traditional finishing systems. The 1C.370 is a precatalyzed vinyl sealer, designed to be used under any precatalyzed or conversion varnish topcoat. It is VOC and HAPs compliant, quick-drying, easy to sand and has excellent adhesion to all interior wood substrates. The 1C.360 Vinyl Sealer is a conventional vinyl sealer designed for use under precatalyzed finishes. It is easy to apply, and achieves smooth, powdery sandability in as little as 15-20 minutes. These sealers, when used in combination with any UltraMax or UltraLaq product makes a finishing system with excellent chemical and moisture resistance.



Code#	Product Description	Glosses Available	Catalyst 1A.822B	Solids (by Wt)	VOC (g/L)	OTC	Viscosity (#2 Zahn)	Recoat	Clean-up	Dry Color	Flash Point
1D.35X	UltraMax™ High Solids WW Precat Lacquer	90+, 60, 40, 20, 10	8 oz / 5 gal	31%	<620	Yes	26-29"	25-35 Min	Lac Thinner	WW	24
1D.33X	UltraLaq™ Premium WW Precat Lacquer	90+, 60, 40, 20, 10	n/a	28%	<660	Yes	26-30"	25-35 Min	Lac Thinner	WW	38
1C.370	UltraLaq™ Premium Vinyl Precat Sealer	n/a	n/a	25%	<680	Yes	25-28"	20-30 Min	Lac Thinner	WW	24
1C.360	UltraLaq™ Premium Vinyl Sealer	n/a	n/a	22%	<680	No	26-30"	20-30 Min	Lac Thinner	WW	17
1M.80X	UltraLaq™ Premium White Precat Topcoat	80+, 60, 40, 20	n/a	43%	<620	Yes	41-49"	30-45 Min	Lac Thinner	White	36
1C.800	UltraLaq™ Premium White Precat Primer	n/a	n/a	41%	<620	Yes	17-27"	25-35 Min	Lac Thinner	White	23

LENMAR™
FINE WOOD FINISHES

4701 O'Donnell Street Baltimore, Maryland 21224 Toll Free: 800-966-7020 www.lenmar-coatings.com